

## Features and Benefits

- Completely sealed
- Totally submersible
- No moving parts
- Easy to use
- Safe & reliable
- Meets toughest NEMA standards

## Description

DuraPoint® - The World's Toughest "Mouse"

Spill on it, smash it, soak it, drop it, whatever! DuraPoint, constructed of stainless steel and heavy rubber, is the world's only fully sealed and submersible mouse. DuraPoint is impervious to liquids and contaminants, earning it the toughest industrial equipment ratings - NEMA 4x, 6P and 13.

Potted solid, DuraPoint is resistant to vibration, shock, ESD, and EMI. And unlike conventional mice and trackballs, DuraPoint has no moving parts to break, wear out, or be cleaned - it's maintenance free! Best of all, DuraPoint is easy and intuitive to use. A simple touch on the mouse button give simultaneous control of both cursor direction and speed.

DuraPoint is the ideal, computer pointing solution for factories, warehouses, service bays, operating rooms, field use, and yes, even dirty desktops.



## Device Characteristics

<b>Compatibilities</b>	Hardware Interface	RS-232 serial port, PS/2® mouse port
	Operating System Compatibilities	PS/2 compatible operating systems
	Serial Data Format	Emulates Microsoft two-button mouse
	Power Consumption	Less than 10mA @ 5V DC
<b>Physical</b>	Physical Size	5.0" x 4.25" x 1.0" (12.8 x 10.8 x 2.5cm)
	Weight	2.0lb (900 grams) including cable
	Primary Materials	Stainless steel, silicone rubber buttons, and silicone potting material
	Cables	STANDARD - 6 ft. (1.8m) shielded cable w/ 9-pin D-sub serial connector (PS/2 adapter included) ENCLOSURE MOUNT - Per standard cable, but includes in-line, low-profile disconnect for use with enclosure cord grips
	Mounting Options	Can be mounted horizontally (desktop) or vertically (panel mount). Four 10-32 inserts are provided on underside for mounting security
<b>Performance</b>	Cursor Directional Control	Continuous 360° control
	Cursor Speed Control	Continuously variable - proportional to applied pressure
	Lifetime	Greater than 10 million cycles
<b>Environmental</b>	Temperature	OPERATING: 32°F (0°C) to 140°F (60°C) STORAGE: -40°F (-40°C) to 185°F (85°C)
	Liquores/Humidity Resistance	Meets NEMA 4X, 6P and 13 standards - completely sealed & submersible
	Particulate/Dust Resistance	Meets NEMA 12 standard - completely sealed against dust & particulates
	Chemical Resistance	Bleach, soap, alcohol, saline, Cidex 7...
	Vibration	OPERATING: 0.5G peak acceleration, 5-500 Hz
	ESD	STORAGE: 5.0G peak acceleration, 5-500Hz
	1 year limited warranty	IEC 801-2, Level 3

## Contact Us

### United States Corporate Office

Interlink Electronics, Inc.  
31248 Oak Crest Drive  
Suite 110  
Westlake Village, CA 91361 USA  
Phone: +1 (805) 484-8855  
Fax: +1 (805) 484-9457  
www.interlinkelectronics.com  
Sales & Support: sales@iefsr.com